



Compressible Flow TME085

Compressible Inviscid Fluid Flow Equations

Alternative Forms of the Energy Equation

Division of Fluid Dynamics
Department of Mechanics and Maritime Sciences
Chalmers University of Technology

The Governing Equations on Differential Non-Conservation Form

Continuity:

$$\frac{D\rho}{Dt} + \rho(\nabla \cdot \mathbf{v}) = 0 \quad (1)$$

Momentum:

$$\frac{D\mathbf{v}}{Dt} + \frac{1}{\rho}\nabla p = \mathbf{f} \quad (2)$$

Energy:

$$\rho \frac{De_o}{Dt} + \nabla \cdot (p\mathbf{v}) = \rho \mathbf{f} \cdot \mathbf{v} + \dot{q}\rho \quad (3)$$

Internal Energy Formulation

Total internal energy is defined as

$$e_o = e + \frac{1}{2}\mathbf{v} \cdot \mathbf{v}$$

Inserted in Eqn. 3, this gives

$$\rho \frac{De}{Dt} + \rho \mathbf{v} \cdot \frac{D\mathbf{v}}{Dt} + \nabla \cdot (p\mathbf{v}) = \rho \mathbf{f} \cdot \mathbf{v} + \dot{q}\rho$$

Now, let's replace the substantial derivative $D\mathbf{v}/Dt$ using the momentum equation on non-conservation form (Eqn. 2).

$$\rho \frac{De}{Dt} - \mathbf{v} \cdot \nabla p + \cancel{\rho \mathbf{f} \cdot \mathbf{v}} + \nabla \cdot (p\mathbf{v}) = \cancel{\rho \mathbf{f} \cdot \mathbf{v}} + \dot{q}\rho$$

Now, expand the term $\nabla \cdot (p\mathbf{v})$ gives

$$\rho \frac{De}{Dt} - \cancel{\mathbf{v} \cdot \nabla p} + \cancel{\mathbf{v} \cdot \nabla p} + p(\nabla \cdot \mathbf{v}) = \dot{q}\rho \Rightarrow \rho \frac{De}{Dt} + p(\nabla \cdot \mathbf{v}) = \dot{q}\rho$$

Divide by ρ

$$\frac{De}{Dt} + \frac{p}{\rho}(\nabla \cdot \mathbf{v}) = \dot{q} \quad (4)$$

Conservation of mass gives

$$\frac{D\rho}{Dt} + \rho(\nabla \cdot \mathbf{v}) = 0 \Rightarrow \nabla \cdot \mathbf{v} = -\frac{1}{\rho} \frac{D\rho}{Dt}$$

Insert in Eqn. 5

$$\frac{De}{Dt} - \frac{p}{\rho^2} \frac{D\rho}{Dt} = \dot{q} \Rightarrow \frac{De}{Dt} + p \frac{D}{Dt} \left(\frac{1}{\rho} \right) = \dot{q}$$

$$\frac{De}{Dt} + p \frac{D\nu}{Dt} = \dot{q} \quad (5)$$

Compare with the first law of thermodynamics: $de = \delta q - \delta w$

Enthalpy Formulation

$$h = e + \frac{p}{\rho} \Rightarrow \frac{Dh}{Dt} = \frac{De}{Dt} + \frac{1}{\rho} \frac{Dp}{Dt} + p \frac{D}{Dt} \left(\frac{1}{\rho} \right)$$

with De/Dt from Eqn. 5

$$\frac{Dh}{Dt} = \dot{q} - \cancel{p \frac{D}{Dt} \left(\frac{1}{\rho} \right)} + \frac{1}{\rho} \frac{Dp}{Dt} + \cancel{p \frac{D}{Dt} \left(\frac{1}{\rho} \right)}$$

$$\frac{Dh}{Dt} = \dot{q} + \frac{1}{\rho} \frac{Dp}{Dt} \quad (6)$$

Total Enthalpy Formulation

$$h_o = h + \frac{1}{2}\mathbf{v}\mathbf{v} \Rightarrow \frac{Dh_o}{Dt} = \frac{Dh}{Dt} + \mathbf{v} \cdot \frac{D\mathbf{v}}{Dt}$$

From the momentum equation (Eqn. 2)

$$\frac{D\mathbf{v}}{Dt} = \mathbf{f} - \frac{1}{\rho}\nabla p$$

which gives

$$\frac{Dh_o}{Dt} = \frac{Dh}{Dt} + \mathbf{v} \cdot \mathbf{f} - \frac{1}{\rho}\mathbf{v} \cdot \nabla p$$

Inserting Dh/Dt from Eqn. 6 gives

$$\frac{Dh_o}{Dt} = \dot{q} + \frac{1}{\rho} \frac{Dp}{Dt} + \mathbf{v} \cdot \mathbf{f} - \frac{1}{\rho} \mathbf{v} \cdot \nabla p = \frac{1}{\rho} \left[\frac{Dp}{Dt} - \mathbf{v} \cdot \nabla p \right] + \dot{q} + \mathbf{v} \cdot \mathbf{f}$$

The substantial derivative operator applied to pressure

$$\frac{Dp}{Dt} = \frac{\partial p}{\partial t} + \mathbf{v} \cdot \nabla p$$

and thus

$$\frac{Dp}{Dt} - \mathbf{v} \cdot \nabla p = \frac{\partial p}{\partial t}$$

which gives

$$\frac{Dh_o}{Dt} = \frac{1}{\rho} \frac{\partial p}{\partial t} + \dot{q} + \mathbf{v} \cdot \mathbf{f}$$

If we assume adiabatic flow without body forces

$$\frac{Dh_o}{Dt} = \frac{1}{\rho} \frac{\partial p}{\partial t}$$

If we further assume the flow to be steady state we get

$$\frac{Dh_o}{Dt} = 0$$

This means that in a steady-state adiabatic flow without body forces, total enthalpy is constant along a streamline.